

The AIRTECH vacuum bagging range is extremely comprehensive, including nylon bagging films, release films, breather/bleeders, sealant tapes, infusion mediums and vacuum connections.

Wrightlon® is a very durable nylon film with good strength and elongation. Wrightlon has great drapeability and works with all resin systems (excluding phenolic).

Suitable for vacuum infusion where bag film thickness and toughness is required.



Wrightlon WL7400 - MECHANICAL DATA		
Elongation at break	%	400
Tensile Strength	psi	8,000
Maximum use temp.	°C	204
Flammability (Self extinguishing)	-	Yes
Colour	-	Green
Resin suitability	-	Epoxy,Polyester,Vinyl Ester

Wrightlon WL6400 - MECHANICAL DATA		
Elongation at break	%	375
Tensile Strength	psi	8,000
Maximum use temp.	°C	204
Flammability (Self extinguishing)	-	Yes
Colour	-	Yellow
Resin suitability	-	Epoxy,Polyester,Vinyl Ester

Order Code	Description	Film Thickness	Form	Width	Roll Length
5-WL740152	Wrightlon 7400	0.050 mm	Sheet	1520 mm	50 m
0-WL740152	Wrightlon 7400	0.050 mm	Sheet	1520 mm	305 m
5-WL640304	Wrightlon 6400	0.050 mm	Sheet	3040* mm	50 m
0-WL640304	Wrightlon 6400	0.050 mm	Sheet	3040* mm	305 m
5-WL64009T	Wrightlon 6400	0.050 mm	Lay Flat Tube	915 mm	50 m
0-WL64009T	Wrightlon 6400	0.050 mm	Lay Flat Tube	915 mm	305 m
5-WL74015T	Wrightlon 7400	0.050 mm	Lay Flat Tube	1500 mm	50 m
0-WL74015T	Wrightlon 7400	0.050 mm	Lay Flat Tube	1500 mm	305 m

* Packaged with centre fold to 1520 mm.

STORAGE

Wrightlon® products should be stored on packaging roll, and kept dry and clean.

NOTE Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty or merchantability or fitness, nor is protection from law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special or consequential damages. 10/12/13