

Data Sheet

AIRSEAL 2

Economical vacuum bag sealant tape

DESCRIPTION

Airseal 2 is a cost effective vacuum bag sealant tape for room and medium temperature applications. Airseal 2 has been specially formulated to provide excellent tack, firm feel, good clean-up and long shelf life. It can also be used for higher temperature envelope bag applications.

Airseal 2 - Standard tack version.

Airseal 2 Tacky - Superior tack for colder environments.

Airseal 2 Super Tacky - Very soft and very high tack version.

BENEFITS

- Lower material cost.
- Long shelf life reduces waste.
- Tacky version has better tack for colder environments.

TECHNICAL DATA

| | |
|-------------------------|---|
| Colour | Black |
| Base material | Synthetic rubber |
| Maximum use temperature | 150°C (300°F) (bag to tool) 180°C (356°F) (bag to bag) |
| Shelf life | 24 months from the date of manufacture |
| Storage conditions | Tape must be stored flat in original packaging at 22°C (72°F) Do not refrigerate |

SIZES

| Dimensions | Dimensions | Packaging |
|---------------------------------|---------------------|-------------------|
| 1/8 inch x 1/2 inch x 49.2 feet | 3 mm x 12 mm x 15 m | 20 rolls per case |
| 1/8 inch x 1/3 inch x 49.2 feet | 3 mm x 9 mm x 15 m | 20 rolls per case |



SUSTAINABILITY



Reduce waste with lower gauge



Recyclable packaging

NOTES

- For clean removal from molds, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.
- The thickness and width are nominal values with associated nominal tolerance range and are not intended for specification purposes.

Last updated : 2025-05-31

Catalog position : [Vacuum bag sealant tapes](#)