

# Vacuum Bag Film

VABATEC®

VABALON 120

VABATEC® 120 is a flexible coextruded multi-layer vacuum bagging film that is designed for resin infusion into the wind power and the boat building industry.

VABALON® 120 is an inexpensive vacuum bagging film, which can be used with all standard resin systems.

## PHYSICAL PROPERTIES

	Unit	Average	Method
Tensile strength (md)	MPa	> 50	ASTM D 882
Tensile strength (cd)	MPa	> 45	ASTM D 882
Elongation at break (md)	%	> 450	ASTM D 882
Elongation at break (cd)	%	> 450	ASTM D 882
Max. temperature 120 °C			

## PACK SIZES

Order Code	Desc.	Length	Width (mm)	Thickness	Format
0-V12760S	Vacuum Bag Film	125 Lm	6000	70 Micron	Sheet
0-V12740S	Vacuum Bag Film	100 Lm	4000	70 Micron	Sheet

## STORAGE

VABALON® 120 should be stored in original packaging, and kept dry and clean.

NOTE: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special or consequential damages. 01.05.2024