

PART No. AS15B

AIRSEAL® 1

SEALANT TAPE



DESCRIPTION

Airseal 1 is an economical multi-purpose sealant tape for room and medium temperature applications. Airseal 1 is suitable for cure applications up to 120°C (248°F). It has a good tack level so secure seals and strong bag hold can be achieved even in colder environments.

BENEFITS

- Economical vacuum tape lowers cost of vacuum bag materials, reducing total cost of manufacture.
- One tape does all with easy to use, multi-purpose tape can be used on multiple tool types and processes.
- Clean removal from tools avoids additional cost of tool cleaning.

TECHNICAL DATA

MATERIAL TYPE	Synthetic rubber
COLOUR	Black
MAXIMUM USE TEMPERATURE	120°C
SHELF LIFE	18 months from date of manufacture
STORAGE	Tape must be stored flat in original packaging at 22°C (72°F). Do not refrigerate.

DESCRIPTION	THICKNESS MM	WIDTH MM	LENGTH LM
AIRSEAL 1 TACKY TAPE – 20 ROLLS PER CARTON	3	12	15

NOTES

- For clean removal, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.
- The thickness and width are nominal values with associated nominal tolerance range and are not intended for specification purposes.

DISCLAIMER

The information in this Technical Data Sheet is provided in good faith as general guidance only. Values stated are typical properties and should not be interpreted as guaranteed performance, specification limits, or design data. Product performance may vary depending on manufacturing processes, application methods, service conditions, storage, handling, and other factors beyond the control of ATL Composites Pty Ltd.

ATL products are intended for sale to industrial and commercial customers. Users are responsible for determining product suitability for their intended application and should conduct their own testing prior to use. ATL Composites Pty Ltd makes no express or implied warranties, including merchantability or fitness for purpose. ATL Composites Pty Ltd shall not be liable for any indirect, special, consequential, or economic loss.