

Part No. P4110
FLOWSTRIP
 RESIN FEED CHANNEL



DESCRIPTION

Flowstrip is a lay flat resin feed channel constructed with a high-speed 3D mesh inside a highly porous non-woven polyester sleeve. Flowstrip is an extremely efficient resin flow channel which is easy to position on infusion laminates and vacuum bag.

BENEFITS

- Good resin flow speeds for reduced infusion cost.
- Easily stored, unrolled, cut and positioned in the mould for faster builds.
- Lays flat for easy vacuum bagging and simple to connect to with Airtech infusion connectors.

TECHNICAL DATA

MATERIAL TYPE	PP mesh in polyester sleeve
COLOUR	Grey
MAXIMUM USE TEMPERATURE	155°C
MATERIALS TO AVOID	Compatible with most resin systems
SHELF LIFE	Unlimited when stored in original packaging at 22°C

DESCRIPTION	WIDTH MM	LENGTH LM	FORM LM
FLOWSTRIP LAY-FLAT RESIN FEED CHANNEL	100	100	LAY FLAT TUBE

NOTES

- The maximum use temperature is process dependent; Airtech recommends testing prior to use.
- Flowstrip is not self-releasing and should be used in conjunction with a perforated release film or peel ply if removal is required after cure.

DISCLAIMER

The information in this Technical Data Sheet is provided in good faith as general guidance only. Values stated are typical properties and should not be interpreted as guaranteed performance, specification limits, or design data. Product performance may vary depending on manufacturing processes, application methods, service conditions, storage, handling, and other factors beyond the control of ATL Composites Pty Ltd.

ATL products are intended for sale to industrial and commercial customers. Users are responsible for determining product suitability for their intended application and should conduct their own testing prior to use. ATL Composites Pty Ltd makes no express or implied warranties, including merchantability or fitness for purpose. ATL Composites Pty Ltd shall not be liable for any indirect, special, consequential, or economic loss.