

Part No. 0V900

RESINFLOW60®

FLOW MEDIA



DESCRIPTION

Resinflow 60 is designed to assist resin flow through your part during the VARTM (Vacuum Assisted Resin Transfer Molding) process. Our resin distribution medium works well with polyester, vinylester and epoxy resins. Resin flows more easily throughout your lay-up, when using Resinflow 60.

TECHNICAL DATA

MATERIAL TYPE	LDPE/HDPE Blend
COLOUR	Red
CONFIGURATION OF NET	Extruded
MAXIMUM USE TEMPERATURE	100°C
MESH WEIGHT	160 g/m ²
SHELF LIFE	Unlimited when stored in original packaging at 22°C

DESCRIPTION	WIDTH MM	LENGTH LM
GREENFLOW75 MESH & WL3700 RELEASE FILM P16	1520	106

DISCLAIMER

The information in this Technical Data Sheet is provided in good faith as general guidance only. Values stated are typical properties and should not be interpreted as guaranteed performance, specification limits, or design data. Product performance may vary depending on manufacturing processes, application methods, service conditions, storage, handling, and other factors beyond the control of ATL Composites Pty Ltd.

ATL products are intended for sale to industrial and commercial customers. Users are responsible for determining product suitability for their intended application and should conduct their own testing prior to use. ATL Composites Pty Ltd makes no express or implied warranties, including merchantability or fitness for purpose. ATL Composites Pty Ltd shall not be liable for any indirect, special, consequential, or economic loss.