

Part No. V740T

VENTURI VACUUM GENERATOR



DESCRIPTION

The Airvac 22 is a venturi block with a self contained silencer that uses compressed shop air lines to create vacuum without the use of a vacuum pump. Airvac 22 will quietly draw up to 25.5 in. Hg (86.4 kPa). The maximum vacuum is achieved at a positive air pressure of 80 psi (5.5 bar). Going above or below this input pressure will decrease the Venturi vacuum potential.

BENEFITS

- Lowest cost vacuum source for workshops.
- Small and portable, the Airvac 22 can be easily carried in tool bags.
- Perfect solution for field repair work.

TECHNICAL DATA

CONNECTIONS

3/8" Hose Barb
 1/4" Nitto Quick Release

DESCRIPTION

FUNCTION

VENTURI VACUUM GENERATOR

COMPRESSED-AIR VACUUM GENERATION

DISCLAIMER

The information in this Technical Data Sheet is provided in good faith as general guidance only. Values stated are typical properties and should not be interpreted as guaranteed performance, specification limits, or design data. Product performance may vary depending on manufacturing processes, application methods, service conditions, storage, handling, and other factors beyond the control of ATL Composites Pty Ltd.

ATL products are intended for sale to industrial and commercial customers. Users are responsible for determining product suitability for their intended application and should conduct their own testing prior to use. ATL Composites Pty Ltd makes no express or implied warranties, including merchantability or fitness for purpose. ATL Composites Pty Ltd shall not be liable for any indirect, special, consequential, or economic loss.